



# TECHNICAL DATA SHEET

## DURASKIRT™ PREMIUM JOINT CONCEALER CAULKING

12842 State Route 9, MOUNT VERNON, WA 98273

Phone: 360-964-9238

Last Updated: January 1, 2025

### DURASKIRT™ PREMIUM JOINT CONCEALER CAULKING

- Color Matched to DURASKIRT™ Concrete Panels
- Durable and Flexible
- Waterproof, Weather-Resistant Seal
- Paintable Surface
- Easy Water Clean-Up
- Resistance to Gas, Oil, Grease, and Salt

**Packaging:** 10.1 fluid ounces (300 mL)

**Color:** Gray

**UPC Number:** 9 08098 90009 9



### Company Identification:

Manufacturer: DURASKIRT., 12842 State Route 9, MOUNT VERNON, WA 98273.

Usage Information: DURASKIRT Help: visit <https://duraskirt.com/concrete-joint-sealant/> and click on "Ask the Expert."

**Order Information:** [duraskirt.com/concrete-joint-sealant](https://duraskirt.com/concrete-joint-sealant)

**Fax Number:** 360-419-9812

**Email:** [RichardImus@Duraskirt.com](mailto:RichardImus@Duraskirt.com)

### Product Description:

**DURASKIRT™ PREMIUM JOINT CONCEALER CAULKING** is a color matched caulking / joint concealer specifically formulated for DURASKIRT™, SDG™ and DURASHEDSKIRT™ concrete joints that are above or below grade. Additionally, it can be used for repairing cracks and holes in concrete, mortar, and masonry. It includes silicone additives to enhance adhesion and water resistance. The sealant forms a durable, flexible, and watertight seal, and it is resistant to gas, oil, grease, and salt. Suitable for both interior and exterior use. It is paintable and can be cleaned up with water.

### Suggested Uses:

Fill cracks, around pipe penetrations & gaps in vertical panel joints in:

- ✓ SDG™ Concrete Panel    ✓ DURASKIRT™ Concrete Panels    ✓ DURASHEDSKIRT™ Concrete Panels

Great Adhesion to DURASKIRT™, SDG™ & DURASHEDSKIRT™ Concrete Panels

### Performance Characteristics:

- Ready to use, no mixing needed.
- Resistant to UV light, rain, snow, and extreme temperatures.
- Durable repair, resistant to gasoline, salt, grease, and oil.
- Mildew resistant when cured.
- Contains no flammable or toxic solvents.
- Easy water clean-up.

### Warranty Information:

If unsatisfied with performance, return the used container and receipt to DURASKIRT. (Note: if provided in an SDG, DURASHEDSKIRT or DURASKIRT kit there will be no refund), Technical Customer Service, PO BOX 97, MOUNT VERNON, WA 98273, for a replacement or refund. DURASKIRT is not liable for incidental or consequential damages.



# TECHNICAL DATA SHEET

## DURASKIRT™ PREMIUM JOINT CONCEALER CAULKING

12842 State Route 9, MOUNT VERNON, WA 98273

Phone: 360-964-9238

### Surface Preparation & Application:

- Ensure the surface is clean, dry, and free from loose concrete.
- Cut the nozzle at a 45° angle to the required bead size.
- Load cartridge into a caulk gun.
- Fill cracks and gaps with sealant.
- Use a wet towel or putty knife for a smooth finish.
- Wipe excess sealant with damp cloth within 30 minutes.
- Remove cured sealant by cutting or scraping.

### For Best Results:

- Apply when temperatures are above 40°F. Avoid rain or freezing conditions.
- Not for underwater use/once cured, sealant can be backfilled with occasional ground moisture.
- Joint size should not exceed 1/2" x 1/2". Use foam backer rod for larger joints.
- Paintable after 2 hours (longer in cool or humid conditions) with latex or oil-based paints.
- Allow 24 hours before exposure to water; cure time is longer in cooler or humid conditions.
- Fully cured in 7-14 days, depending on temperature, humidity, and fill depth.
- Store away from extreme heat or cold.

### Physical & Chemical Characteristics:

- **Vehicle:** Acrylic Emulsion
- **Volatile:** Water
- **Pigment:** Calcium Carbonate
- **Solids:** 82% ± 1% by weight
- **Weight Per Gallon:** 13.6 lbs. ± 0.02 lbs.
- **Service Temperature:** -30°F to 150°F
- **Freeze/Thaw Stability:** Passes 5 Cycles
- **Consistency:** Smooth
- **Shelf Life:** 36 months
- **Coverage:** 56 linear feet at 3/16" diameter bead
- **MSD No:** 00010010001

### Clean Up:

Wipe off excess uncured sealant with a damp cloth within 30 minutes. Cut or scrape away dried material.

### Safety:

For safety details, check the product label or MSD. Request an MSDS by visiting [duraskirt.com/msdPremiumJointConcealerCaulking](http://duraskirt.com/msdPremiumJointConcealerCaulking)

### Warranty Information:

If unsatisfied with performance, return the used container and receipt to DURASKIRT. (Note: if provided in an SDG, DURASHEDSKIRT or DURASKIRT kit there will be no refund), Technical Customer Service, PO BOX 97, MOUNT VERNON, WA 98273, for a replacement or refund. DURASKIRT is not liable for incidental or consequential damages.

